



MKE 40 Clip-On Microphone



The MKE 40 is a high-quality, clip-on microphone for every area of live sound transmission. Its consistent pick-up pattern (cardioid) ensures high feedback rejection and excellent acoustic performance under challenging on-stage conditions. It sets the highest benchmarks in sound quality and robustness under tough on-stage conditions.

FEATURES

- High gain before feedback
- Very good speech intelligibility
- Outstanding bass reproduction
- Pronounced directivity
- Small dimensions
- Insensitive to structure-borne noise
- Balanced frequency response

DELIVERY INCLUDES

- MKE 40 microphone
- MZW 40 windshield, black
- MZW 40 windshield, grey
- MZM 2/MZM 10 magnetic mount set
- clip, black
- instruction manual

PRODUCT VARIANTS


Variant	Connector	Applicable to	Article number
MKE 40-4	3-pin SE	SK 50/SK 250/SK 6000/ SK 9000/SK 2000/SK 5212	Art. no. 003579
MKE 40-ew	3.5 mm jack	ew G3/ew G4/ew D1/ SpeechLine DW/XSW	Art. no. 500527




MKE 40

Clip-On Microphone

FREQUENCY RESPONSE



POLAR PATTERN



SPECIFICATIONS

Transducer principle	pressure gradient transducer
Pick-up pattern	cardioid
Sensitivity	42 mV/Pa, ± 2.5 dB (1 kHz)
Rated impedance	approx. 3 k Ω
Min. terminating impedance	15 k Ω
Max. SPL at 1 kHz	118 dB
Frequency response	40 to 20,000 Hz
Equivalent noise level A-weighted (DIN IEC 651)	27 dB
Equivalent noise level CCIR-weighted (CCIR 468-1)	37 dB
Connector	see product variants
Cable length	MKE 40-4: approx. 1.60 m MKE 40-ew: approx. 1.10 m
Dimensions	\varnothing 12 mm, length: 26 mm